

# RS PRO P2 flat S

warm white  
EAN 4007841 069742  
Article number 069742



LED

36 Jahre (Ø 4,5 Std / Tag)



Innenleuchte



Hochfrequenz Sensor 360°



Max. 8 m



2 - 2000 Lux



Vernetzbar via Kabel



Manuelle Übersteuerung 4 Std



Lichtquelle nicht austauschbar



Betriebsgerät nicht austauschbar



IP54

## Function description

Circular classic. Perfect shape. Perfect efficiency. The perfect switched indoor light. The RS PRO P2 flat S integrates harmoniously into corridors, hallways and stairwells. It combines timeless design and extremely easy installation with pioneering technology and unbeatable efficiency. High-precision 360° HF sensor for reliable detection (8 m reach). In addition, two metal discs are always included to further limit the sensor in certain directions. As many as ten lights can be interconnected by cable. Output: 15,1 W with 1608 lm, 3000 K.

## Technical specifications

Dimensions (Ø x H)	322 x 68 mm	Soft light start	Yes
With lamp	Yes, STEINEL LED system	Twilight setting	2 – 2000 lx
With motion detector	Yes	Time setting	5 s – 15 Min.
Manufacturer's Warranty	5 years	Basic light level function	Yes
Version	warm white	Basic light level function time	10/30 min, all night
PU1, EAN	4007841069742	Main light adjustable	No
Colour	white	Interconnection	Yes
Installation site	wall, ceiling	Interconnection via	Cable
Installation	Ceiling	Lifetime LED according to IEC-62717 (L70)	100.000 h
Impact resistance	IK03	Lifetime LED according to IEC-62717 (L80)	73.000 h
IP-rating	IP54	Lebensdauer LED nach IES TM-21 (L70)	>60.000 h
Protection class	II	Lifetime LED according to IES TM-21 (L80)	>60.000 h
Ambient temperature	-10 – 40 °C	Fuse protection B10	54
Housing material	Plastic	Fuse protection B16	87
Cover material	Plastic, opal		
Mains power supply	220 – 240 V / 50 – 60 Hz		

# RS PRO P2 flat S

warm white  
 EAN 4007841 069742  
 Article number 069742



## Technical specifications


Mounting height max.	4,00 m
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	Ø 8 m (50 m <sup>2</sup> )
Reach, tangential	Ø 8 m (50 m <sup>2</sup> )
Luminous flux total product	1608 lm
Total product efficiency	107 lm/W
Colour temperature	3000 K
Lamp	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control

Fuse protection C10	90
Fuse protection C16	145
Switching output 1, low-voltage halogen lamps	800 VA
LED lamps > 8 W	250 W
Capacitive load in µF	88 µF
Basic light level function in per cent	10 %
Output	15,1 W
Colour Rendering Index CRI	= 82
Photobiological safety in accordance with EN 62471	RG1
Starting current, maximum	13 A
IP-rating, ceiling	IP54
Detection angle	360 °

# RS PRO P2 flat S


warm white  
EAN 4007841 069742  
Article number 069742

## Detection Zone




Possible mounting height: 2,00 m - 4,00 m  
Orange: radial and tangential

## Dimension Drawing




## Light Distribution Curve



<b>Output</b>	15,1 W
<b>With lamp</b>	Yes, STEINEL LED system
<b>Lamp</b>	LED cannot be replaced
<b>Measured luminous flux (360°)</b>	1608 lm
<b>Colour temperature</b>	3000 K
<b>LED life expectancy (max. °C)</b>	50000 h
<b>LED cooling system</b>	Passive Thermo Control

## Master circuit diagram




# RS PRO P2 flat S

warm white  
EAN 4007841 069742  
Article number 069742



**Master/master interconnection circuit diagram**



**Master/slave interconnection circuit diagram**

