XLED PRO ONE Max

without motion detector - white EAN 4007841 086824 Article number 086824







3000 K

















Langlebige LED 50.000 h

3000K warmweiß

IP44

Panel 180° vertikal

Betriebsgerät nicht austauschbar Lichtquelle nicht austauschbar

Function description

Floodlight redefined. The XLED PRO ONE floodlight without sensor, which can be swivelled vertically through 180° and comes in a stylish aluminium housing, ensures daylight illumination of large areas with warm white 3000 K and 6093 lm at 49,4 W. Suitable for manual switch operation and for cablebased networking in conjunction with a sensor version. With optional surface-mounted adapter. Available in white or anthracite. 5-year guarantee.

Technical specifications

Dimensions (L x W x H)	202 x 259 x 226 mm	
With lamp	Yes, STEINEL LED system	
With motion detector	No	
Manufacturer's Warranty	5 years	
Version	without motion detector - white	
PU1, EAN	4007841086824	
Application, place	Outdoors	
Application, room	outdoors, garden, front door, courtyard & driveway, all round the building	
Colour	white	
Includes corner wall mount	No	
Installation site	ceiling, wall	
Installation	Surface wiring, Wall	
Impact resistance	IK03	
IP-rating	IP44	
Protection class	I	
Ambient temperature	-20 – 40 °C	

Photo-cell controller	No
Cover material	shrouds
Luminous flux total product	6093 lm
Measured luminos flux (360°)	6093 lm
Total product efficiency	123 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM3
Lamp	LED cannot be replaced
Service life LED L70B50 (25°)	> 36000 h
LED cooling system	Passive Thermo Control
Functions	Relay output
Basic light level function	No
Main light adjustable	No
Twilight setting TEACH	No
Interconnection	Yes
Type of interconnection	Master/slave
Interconnection via	Cable

LED floodlight without sensor - Professional Line

XLED PRO ONE Max

without motion detector - white EAN 4007841 086824 Article number 086824



Technical specifications

Housing material	Aluminium	Output	49,4 W
Cover material	Glass transparent	Colour Rendering Index CRI	= 80
Mains power supply	220 – 240 V / 50 – 60 Hz		

Accessories


EAN 4007841 080983	Surface mount adapter XLED PRO ONE Plus + Max
EAN 4007841 079000	RC 12

XLED PRO ONE Max

without motion detector - white EAN 4007841 086824 Article number 086824



Dimension Drawing



Slave circuit diagram

Subject to technical modifications



Master/slave interconnection circuit diagram

