

Data sheet


SENSOTEC Sensor IPD

HB PIR 3360 IPD




110088245 SENSOTEC Sensor HB PIR 3360 IPD Intra
 110088246 SENSOTEC Sensor HB PIR 3360 IPD Wire
 110088247 SENSOTEC Sensor HB PIR 3360 IPD Zhaga



A head for heights. Powerful reach. Reliable. Ideal for high ceilings in industrial buildings or commercial properties.



Technical specifications

DALI instances	Occupancy sensor (type 3) / Light sensor (type 4)		
Sensor technology	Passive infrared technology		
3D data	available online		
Light measurement range	4 - 1000lx		
Mounting height	2.8 - 14m		
Reach, radial	Ø 14m (154m ²) for mounting height 6m		
Reach, tangential	Ø 36m (1018m ²) for mounting height 6m		
Supply voltage / current consumption	12 - 22.5VDC / max. 16mA		
Temperature range	-20 to +50°C (tc +50°C)		
Interfaces	DALI		
Approval marks / Conformity	CE / DALI-2		
Standards	EN 61347-1 / EN 61347-2-11 / EN 55015 / EN 61547 / EN 62386-101 / EN 62386-103 / EN 62386-303 / EN 62386-304		
Connection options	HB PIR 3360 IPD Intra	HB PIR 3360 IPD Wire	HB PIR 3360 IPD Zhaga
			
GTIN	4007841085414	4007841085421	4007841085438
Type	9016	9022	9021
Dimensions	91.5 × 63.3 × 49mm	91.5 × 63.3 × 49mm	91.5 × 63.3 × 57mm
Connection	0.34 - 0.75mm ²	Connection strands (0.5mm ² , L=250mm, white)	Zhaga Book 18
IP rating	IP20 / IP65 (sealed lens)	IP65	IP65

Note: STEINEL Solutions AG hereby declares that the SENSOTEC NET products comply with Directive 2014/53/EU. The full text of the EU Declaration of Conformity is available at the following link: <https://bit.ly/3NvySr7>

Downloads & further details

[Data sheet SENSOTEC IPD](#)
[3D data](#)
[EU Declaration of Conformity](#)